

RBM 3/20 H

HYDRAULIC ANGLE ROLL WITH 3 MOTORIZED ROLLS
MANUAL ANGLE ROLL WITH 3 MOTORIZED ROLLS



RBM 3/20 H

1 SET OF STANDARD ROLLERS + CONTROL PANEL WITH ELECTRONIC DISPLAY

RBM 3/20 MP




1 SET OF STANDARD ROLLERS + FOOT PEDALS

RBM 3/20 MDP

1 SET OF STANDARD ROLLERS + FOOT PEDALS + ELECTRONIC DISPLAY

RBM 3/20 H

Bending Capacity

SECTION	SIZE		DIAMETER		NOTE
	10x2 25x6	3/8x1 _{1/16} 1x1/4	80 200	3 _{1/2} 8	standard rolls
	20x3 45x10	3/4x1/8 1/3/4x3/8	90 300	4 12	standard rolls
	12	1/2	80	3 _{1/2}	standard rolls
	15x15x3 25x25x4	5/8x5/8x1/8 1x1x1/8	100 120	4 5	standard rolls
	15x15x3 25x25x4	5/8x5/8x1/8 1x1x1/8	100 160	5 6	standard rolls
	25x12x1.5 30x15x4	1x1/2x1/16 1 _{1/8} x5/8x5/32	120 200	5 8	standard rolls
	30x15x4	1 _{1/8} x5x8x5/32	250	10	standard rolls
	20x20x4	3/4x3/4x1/8	200	8	special rolls
	20x20x4	3/4x3/4x1/8	250	10	special rolls
	30x10x1.5	1 _{1/16} x3/8x1/16	250	10	special rolls
	12	1/2	80	3 _{1/2}	special rolls
	10x1.5 3/4 " GAS	3/8x1/16 1 _{1/16}	80 400	3 _{1/2} 16	special rolls
	30x1.5	1 _{1/8} 1/16	400	16	special rolls

TECHNICAL DATA:

- ✓ SHAFTS DIAMETER MM.20 | 13/16"
- ✓ SHAFTS SPEED 12.5 RPM
- ✓ THREE LORMING ROLLS KNURIED
- ✓ APPROXIMATE WEIGHT: KG 90 - LBS 200
- ✓ PACKING DIMENSION MM: B 520X600 - H 600
- ✓ PRESSURE OF THE HYDRAULIC CYLINDER KG 2000 (2 T.)

STANDARD EQUIPMENT:

- ✓ STANDARDS ROLLS
- ✓ LATERAL STRANGHTENERS
- ✓ SERVICE SPANNERS
- ✓ INSTRUCTION MANUAL