

RBM 3/60 H

HYDRAULIC ANGLE ROLL WITH 2 OR 3 MOTORIZED ROLLS
→ ON REQUEST CNC CONTROL VERSION ←



RBM N3/60 H

1 SET OF STANDARD ROLLERS + CONTROL PANEL WITH ELECTRONIC DISPLAY

RBM N2/60 H

1 SET OF STANDARD ROLLERS + CONTROL PANEL WITH ELECTRONIC DISPLAY

RBM 3/60 H

Bending Capacity

SECTION	SIZE		DIAMETER		NOTE
	40x10 80x15	1 1/2x3/8 3 1/4x5/8	280 600	11 24	standard rolls
	50x10 120x25	2x3/8 5x1	300 400	12 26	standard rolls
	20 50	3/4 2	250 600	10 24	standard rolls
	40x40x5 80x80x9	1 1/2x1 1/2x1/8 3 1/8x3 1/8x3/8	350 800	14 30	standard rolls
	40x40x5 80x80x9	1 1/2x1 1/2x1/8 3 1/8x3 1/8x3/8	250 1000	10 40	standard rolls
	60x30x6 120x55x7	1 1/2x1 1/4x1/4 5x2 1/4x1/4	350 600	14 24	standard rolls
	60x3x6 120x55x7	1 1/2x1 1/4x1/4 5x2 1/4x1/4	500 1000	20 40	standard rolls
	40x40x5 70x70x7	1 1/2x1 1/2x1/8 2 3/4x2 3/4x1/4	400 800	16 32	special rolls
	40x40x5 70x70x7	1 1/2x1 1/2x1/8 2 3/4x2 3/4x1/4	600 1000	24 40	special rolls
	40x40x2 80x40x3	1 1/2x3/4x1/16 2 3/4x1 1/2x1/8	400 1200	24 40	special rolls
	20 50	3/4 2	300 600	12 24	special rolls
	33x2.6 88.9x3.2	1 1/4 - (1*GAS) 3 1/2 - (3*GAS)	400 1500	16 60	special rolls
	100x2	4	1800	70	special rolls

TECHNICAL DATA:

✓ SHAFTS DIAMETER MM.60 | 2-3/8"

✓ SHAFTS SPEED 6 RPM

✓ THREE LORMING ROLLS KNURIED

✓ APPROXIMATE WEIGHT: KG 1210 - LBS 2680

✓ PACKING DIMENSION MM: B 870X1125 - H 1620

✓ PRESSURE OF THE HYDRAULIC CYLINDER KG 18000 (18 T.)

STANDARD EQUIPMENT:

✓ STANDARDS ROLLS

✓ LATERAL STRANGHTENERS

✓ SERVICE SPANNERS

✓ INSTRUCTION MANUAL