


RBM 3/35 H



Special machine for bending aluminum profiles, especially for the door, window and aircraft parts industry. The machine is equipped with two fixed rolls and only one forming roll; thanks to this solution, profile distortion is minimized. All three rollers are motorized

RBM 3/35 H

Bending Capacity

SECTION	SIZE		DIAMETER		NOTE
	20x6	1x3/16	200	6	standard rolls
	50x10	2x3/8	400	14	
	30x6	3/4x1/4	200	7	standard rolls
	80x15	3 1/2x5/8	350	16	
	10	5/8	100	5	standard rolls
	30	1 1/4	600	16	
	20x20x3	3/4x3/4x1/8	250	8	standard rolls
	50x50x8	2x2x5/16	400	14	
	20x20x3	3/4x3/4x1/8	250	8	standard rolls
	50x50x6	2x2x5/16	500	16	
	50x25x5		300	10	standard rolls
				16	
	50x25x5		400	10	standard rolls
				16	
	20x20x3	3/4x3/4x1/8	200	8	special rolls
	45x45x6	1 3/4x1 3/4x1/4	300	12	
	40x40x6	1 1/2x1 1/2x1/4	600	14	special rolls
	25x15x1.5	1x5/8x1/16	250	10	special rolls
	50x30x3	2x1 1/4x1/8	1000	40	
	10	3/8	100	4	special rolls
	30	1 1/4	400	16	
	1/2 " GAS	3/4	200	8	special rolls
	1 1/2 " GAS	2	400	14	
	60x1.5	2 1/2x1/16	800	24	special rolls

TECHNICAL DATA:

✓ SHAFTS DIAMETER MM.35 | 1.38"

✓ SHAFTS SPEED 12.5 RPM

✓ THREE LORMING ROLLS KNURIED

✓ APPROXIMATE WEIGHT: KG 350 - LBS 770

✓ PACKING DIMENSION MM: 900X600X1100

✓ PRESSURE OF THE HYDRAULIC CYLINDER KG: 4000 (4T)

STANDARD EQUIPMENT:

✓ STANDARDS ROLLS

✓ LATERAL STRANGHTENERS

✓ SERVICE SPANNERS

✓ INSTRUCTION MANUAL